

19427/04099

AMENDMENTS TO THE CLAIMS

1. (currently amended) An adjustable wreath hanger comprising:

an elongated hanger strip ~~having comprising~~ comprising an upper end and a downwardly extending end, said upper end comprising a rearwardly facing, resilient door hook, and ~~a said downwardly extending portion end having comprising~~ a plurality of vertically separated, forwardly facing detent members; and

an elongated hook strip ~~having comprising~~ a lower end and an upper end, said lower end comprising a forwardly facing hook member, and said upper portion end comprising a resilient engagement tab having a rearwardly facing projection, a slide member attached to and cooperating with the upper ~~portion end~~ of the hook strip to define an aperture thorough which the downwardly extending ~~portion end~~ of the hanger strip is insertable to create an interfering fit between the rearwardly facing projection of the hook strip and the detent members of the hanger strip, the slide member further comprising an upwardly extending, resilient backing tab spaced apart from the rearwardly facing projection, the resilient backing tab biasing an aligned detent member of the hanger strip into engagement with the rearwardly facing projection of the hook strip to maintain a predetermined vertical separation between the door hook and the forwardly facing hook member during use.

2. (cancelled)

3. (original) The adjustable wreath hanger of claim 1 wherein the backing tab has a top end with a forwardly extending projection that biases the detent member of the hanger strip against the rearwardly facing projection to prevent the hook strip from sliding downwardly in relation to the hanger strip.

4. (original) The adjustable wreath hanger of claim 3 wherein the rearwardly facing projection is selectively disengageable from the detent members of the hanger strip by the application of a rearwardly directed force to the hanger strip at a point above the top of the backing tab.

5. (cancelled)

6. (cancelled)

7. (new) The adjustable wreath hanger of claim 1 wherein the rearwardly facing projection is selectively disengageable from the detent members of the hanger strip by the simultaneous application of a forwardly directed force to the resilient engagement tab and a rearwardly

19427/04099

directed force to the backing tab, thereby enabling the free movement of the hook strip in an upward or downward direction.

8. (new) An adjustable wreath hanger comprising:

an elongated hanger strip comprising an upper end and a downwardly extending end, said upper end comprising a rearwardly facing, resilient door hanger, and said downwardly extending end comprising a series of vertically separated recesses disposed on the forward surface of the hanger strip; and

an elongated hook strip comprising a lower hook end and an upper engagement end, said lower hook end comprising a forwardly facing hook member, and said upper engagement end comprising a slide member comprising a resilient backing tab, and a resilient engagement tab comprising a rearwardly facing projection, and

wherein the slide member defines an aperture thorough which the downwardly extending end of the hanger strip is insertable to align the hanger strip with the hook strip, and

wherein the resilient backing tab of the slide member opposes the rearwardly facing projection of the resilient engagement tab such that when the downwardly extending portion of the hanger strip is inserted into the aperture defined by the slide member the resilient backing tab biases an aligned recess of the hanger strip into engagement with the rearwardly facing projection of the hook strip to maintain a predetermined vertical separation between the door hook and the forwardly facing hook member during use, and

wherein the rearwardly facing projection is selectively disengageable from the detent members of the hanger strip by the simultaneous application of a forwardly directed force to the resilient engagement tab and a rearwardly directed force to the backing tab, thereby enabling the free movement of the hook strip in an upward or downward direction.

9. (new) An adjustable wreath hanger comprising:

a hanger strip comprising:

a top portion having a first and second end,

an elongated first downwardly-extending portion having a first and a second end and attached at its first end to the first end of the top portion and arranged at a

19427/04099

right angle relative to the top portion, the first downwardly extending portion having at its second end a plurality of vertically separated recesses disposed on the second end of the first downwardly-extending portion, and

a second downwardly-extending portion comprising a first and a second end which is attached at its first end to the second end of the top portion, and is arranged at an angle from about 90 degrees to 75.8 degrees relative to the top portion such that the second downwardly-extending portion opposes the first downwardly extending portion; and

a hook strip comprising:

a lower end comprising a forwardly facing hook member, and

an upper end comprising a resilient engagement tab

wherein said engagement tab comprises a rearwardly facing projection, a slide member that defines an aperture thorough which the first downwardly extending portion of the hanger strip is insertable to align the hanger strip with the hook strip to create an interfering fit between the rearwardly facing projection and the recesses of the first downwardly extending portion of the hanger strip, the slide member comprising a resilient backing tab opposing the rearwardly facing projection, the backing tab biasing an aligned recess of the first downwardly extending portion of the hanger strip into engagement with the rearwardly facing projection of the hook strip to maintain a predetermined vertical separation between the door hook and the forwardly facing hook member during use.